

## CLAIMS

What is claimed is:

- 1 1. A method for fine granular scalability encoding, comprising the steps of:
  - 2 (a) repeating, for each individual transform block in an image frame, the steps of:
    - 3 (i) decomposing a respective plurality of residual coefficients for the
    - 4 respective transform block;
    - 5 (ii) processing a respective plurality of bit-planes or discrete quantization
    - 6 steps for the respective transform block before decomposing coefficients
    - 7 for a next one of the transform blocks in the image frame.
- 1 2. The method of claim 1, wherein the transform blocks are discrete cosine
- 2 transform (DCT) blocks, and the residual coefficients are DCT residual coefficients.
- 1 3. The method of claim 2, wherein step (ii) includes run-length and variable length
- 2 coding each of the plurality of bit-planes .
- 1 4. The method of claim 2, wherein step (a) further comprises
- 2 (iii) storing each bit-plane at a respectively different position.
- 1 5. The method of claim 4, wherein each  $b^{\text{th}}$  bit-plane of the  $i^{\text{th}}$  one of the DCT blocks
- 2 is stored in a location immediately following the location of the  $b^{\text{th}}$  bit-plane of the  $i-1^{\text{th}}$
- 3 one of the DCT blocks, where  $b$  is an integer, and  $i$  is an integer greater than one.
- 1 6. The method of claim 2, further comprising:
- 2 (b) forming a compressed bitstream containing the respective plurality of bit-planes
- 3 for all of the DCT blocks in the image frame, wherein the data in the compressed
- 4 bitstream are arranged by bit-plane.
- 1 7. The method of claim 6, wherein:
- 2 step (a) further comprises determining a maximum magnitude of any DCT
- 3 coefficient for the respective DCT block;
- 4 the method further comprises determining a maximum one of the maximum
- 5 magnitudes before step (b); and
- 6 the data from the plurality of bit-planes are arranged in the compressed bitstream
- 7 beginning with the bit-plane corresponding to the maximum one of the maximum
- 8 magnitudes.

- 1 8. The method of claim 6, wherein steps (a) and (b) are performed without requiring  
2 simultaneous storage of all the DCT residual coefficients for the image frame.
- 1 9. The method of claim 1, wherein the plurality of bit-planes includes each bit-plane  
2 from a most significant bit-plane to a least significant bit-plane .
- 1 10. The method of claim 1, wherein the transform blocks are formed by one of the  
2 group consisting of discrete cosine transform, block-based wavelet coding or matching  
3 pursuit and SNR-scalabilities using discrete quantization steps.
- 1 11. Apparatus for fine granular scalability encoding, comprising  
2 means for decomposing a plurality of residual coefficients for an individual  
3 transform block of /an image frame;  
4 scanning and coding means for processing a respective plurality of bit-planes or  
5 discrete quantization steps for the respective transform block before decomposing  
6 coefficients for a next one of the transform blocks in the image frame.
- 1 12. The apparatus of claim 11, wherein the scanning and coding means include  
2 means for scanning blocks in a first sequence and for storing coded data in a second  
3 sequence different from the first sequence.
- 1 13. The apparatus of claim 12, wherein:  
2 the transform blocks are discrete cosine transform (DCT) blocks, and the residual  
3 coefficients are DCT residual coefficients; and  
4 each  $b^{\text{th}}$  bit-plane of the  $i^{\text{th}}$  one of the DCT blocks is stored in a location  
5 immediately following the location of the  $b^{\text{th}}$  bit-plane of the  $i-1^{\text{th}}$  one of the DCT blocks,  
6 where  $b$  is an integer, and  $i$  is an integer greater than one.
- 1 14. The apparatus of claim 11, wherein the apparatus does not have a memory used  
2 for simultaneous storage of all the DCT residual coefficients for the image frame.
- 1 15. The apparatus of claim 11, wherein the decomposing means provides residual  
2 coefficient data for a block directly to the scanning and coding means without storing the  
3 residual coefficient data in an intermediate storage device.
- 1 16. The apparatus of claim 11, wherein the decomposing means provides residual  
2 coefficient data for a block directly to the scanning and coding means without masking  
3 the residual coefficient data to extract data for a single bit-plane from all of the blocks in  
4 the image frame.

1 17. A computer readable medium having computer program code encoded thereon,  
2 wherein, when the computer program code is executed by a processor, the processor  
3 executes a method for fine granular scalability encoding, comprising the steps of:  
4 (a) repeating , for each individual transform block in an image frame, the steps of:  
5 (i) decomposing a respective plurality of residual coefficients for the  
6 respective transform block;  
7 (ii) processing a respective plurality of bit-planes or discrete quantization  
8 steps for the respective transform block before decomposing coefficients  
9 for a next one of the transform blocks in the image frame.

1 18. The computer readable medium of claim 17, wherein the transform blocks are  
2 discrete cosine transform (DCT) blocks, and the residual coefficients are DCT residual  
3 coefficients.

1 19. The computer readable medium of claim 18, wherein step (ii) includes run-length  
2 and variable length coding each of the plurality of bit-planes.

1 20. The computer readable medium of claim 18, wherein  
2 step (a) further comprises storing each bit-plane at a respectively different  
3 position; and  
4 each  $b^{\text{th}}$  bit-plane of the  $i^{\text{th}}$  one of the DCT blocks is stored in a location  
5 immediately following the location of the  $b^{\text{th}}$  bit-plane of the  $i-1^{\text{th}}$  one of the DCT blocks,  
6 where  $b$  is an integer, and  $i$  is an integer greater than one.

1